

IN THE CLAIMS

Please amend the following claims which are pending in the present application:

1. (Currently amended) ~~An optical drive bezel for coupling to an optical drive including~~ apparatus comprising:

a functional bezel having a first opening to receive an optical disk and a first plurality of attachment features, ~~the functional bezel configured to be coupled to the optical drive;~~

~~a disk guide coupled to the functional bezel; and~~

a cosmetic bezel having a second opening to receive the optical disk and second plurality of attachment features, ~~the cosmetic bezel rigidly coupled to the functional bezel,~~ wherein the first opening and the second opening are in alignment,

wherein the functional bezel and the cosmetic bezel are attached to form an integrated optical drive bezel, the integrated optical drive bezel configured to be coupled to an optical drive.

2. (Currently amended) ~~The optical drive bezel apparatus~~ of claim 1 wherein the functional bezel provides structural rigidity for the optical drive.

3. (Currently amended) The ~~apparatus~~optical drive bezel of claim 1 further comprising a cosmetic screen attached to the cosmetic bezel.
4. (Currently amended) The ~~apparatus~~optical drive bezel of claim 1 wherein the functional bezel includes a plurality of mounting points for mounting the functional bezel to the optical drive and for mounting the functional bezel to an enclosure that houses the optical drive.
5. (Currently amended) The ~~apparatus~~optical drive bezel of claim 1 wherein the functional bezel includes a plurality of mounting points for mounting the functional bezel to various configurations of various optical drives.
6. (Currently amended) The ~~apparatus~~optical drive bezel of claim 1 wherein the first plurality of attachment features of the functional bezel matches the second plurality of attachment features.
7. (Currently amended) The ~~apparatus~~optical drive bezel of claim 1 further comprising a disk guide wherein the disk guide facilitates proper attachment of the optical disk into the optical drive.

8. (Currently amended) The ~~apparatus~~optical drive bezel of claim 1 further comprising a disk guide wherein the disk guide includes a ramp feature to point the optical disk down into the optical drive during injection and to point the optical disk up during ejection.
9. (Currently amended) The ~~apparatus~~optical drive bezel of claim 1 wherein the cosmetic bezel includes a recess configured to receive the cosmetic screen.
10. (Currently amended) The ~~apparatus~~optical drive bezel of claim 1 wherein the second opening in the cosmetic bezel is larger than the first opening in the functional bezel to facilitate injection or ejection.
11. (Currently amended) The ~~apparatus~~optical drive bezel of claim 1 wherein the cosmetic screen performs at least one of minimizing contaminants into the optical disk drive and wiping the optical disk as the optical disk is being inserted into the optical drive.
12. (Currently amended) An ~~slot-loading~~optical disk drive assembly comprising:

an optical disk drive;

~~coupled to~~ an optical drive bezel assembly coupled to the optical disk drive, the optical drive bezel assembly having a functional bezel rigidly attached to a cosmetic bezel, wherein a slot is provided in the optical drive bezel assembly to allow an optical disk to pass therethrough and wherein the slot remains open when a disk is in the optical drive, wherein the optical drive bezel assembly is coupled to the optical disk drive.

13. (Currently amended) The ~~slot loading~~ optical disk drive assembly of claim 12 further comprises a cosmetic screen disposed between the functional bezel and the cosmetic bezel, the cosmetic screen fixedly attached to the cosmetic bezel.

14. (Currently amended) The ~~slot loading~~ optical disk drive assembly of claim 12 further comprising a cosmetic screen disposed between the function bezel and the cosmetic bezel, the cosmetic screen fixedly attached to the cosmetic bezel.

15. (Currently amended) The ~~slot loading~~ optical disk drive assembly of claim 14 wherein the functional bezel has a first opening to receive the optical disk and a first plurality of attachment features, the functional bezel coupled to the optical drive, and the cosmetic bezel has a second opening to receive the optical disk and

second plurality of attachment features, wherein the first opening and the second opening are in attachment to form the slot.

16. (Currently amended) The ~~slot loading~~ optical disk drive assembly of claim 14 wherein the functional bezel provides structural rigidity for the optical disk drive.

17. (Currently amended) The ~~slot loading~~ optical disk drive assembly of claim 14 wherein the functional bezel includes a plurality of mounting points for mounting the functional bezel to the optical disk drive.

18. (Currently amended) The ~~slot loading~~ optical disk drive assembly of claim 14 wherein the functional bezel includes a plurality of mounting points configured for mounting the functional bezel to the slot loading optical disk drive.

19. (Currently amended) The ~~slot loading~~ optical disk drive assembly of claim 14 wherein the first plurality of attachment features of the functional bezel matches the second plurality of attachment features.

20. (Currently amended) The ~~slot-loading~~ optical disk drive assembly of claim 14 wherein the disk guide facilitates proper attachment of the optical disk into the optical drive.

21. (Currently amended) The ~~slot-loading~~ optical disk drive assembly of claim 14 wherein the disk guide includes a ramp feature to point the optical disk down into the optical drive during injection and to point the optical disk up during ejection.

22. (Currently amended) The ~~slot-loading~~ optical disk drive assembly of claim 14 wherein the cosmetic bezel includes a recess configured to receive the cosmetic screen.

23. (Currently amended) The ~~slot-loading~~ optical disk drive assembly of claim 14 wherein the second opening in the cosmetic bezel is larger than the first opening in the functional bezel to facilitate injection or ejection of the optical disk.

24. (Currently amended) The ~~slot-loading~~ optical disk drive assembly of claim 14 wherein the cosmetic screen performs at least one of minimizing contaminants

into the optical disk drive and wiping the optical disk as the optical disk is being inserted into the optical disk drive.

25. (Currently amended) A computer system comprising:

an enclosure;

an optical drive coupled to the enclosure;

a functional bezel having a first opening to receive an optical disk and a first attachment feature, ~~the functional bezel coupled to the optical drive and the enclosure;~~

~~a disk guide rigidly coupled to the functional bezel; and~~

a cosmetic bezel having a second opening to receive the optical disk and second attachment feature, the cosmetic bezel rigidly coupled to the functional bezel through a coupling of the first and the second attachment features, wherein the first opening and the second opening are in alignment through the coupling of the first and the second attachment features,

wherein the cosmetic bezel is rigidly coupled to the functional bezel to form an integrated bezel assembly, the integrated bezel assembly coupled to the optical drive and the enclosure.

26. (Previously presented) The computer system of claim 25 wherein the optical drive is rigidly mounted to the enclosure.
27. (Previously presented) The computer system of claim 25 further comprises a cosmetic screen attached to the cosmetic bezel.
28. (Previously presented) The computer system of claim 27 wherein the cosmetic bezel includes a recess configured to receive the cosmetic screen.
29. (Previously presented) The computer system of claim 25 wherein the functional bezel provides structural rigidity for the optical drive.
30. (Previously presented) The computer system of claim 25 wherein the functional bezel includes a plurality of mounting points for mounting the functional bezel to the optical drive.
31. (Previously presented) The computer system of claim 25 wherein the functional bezel includes a plurality of mounting points configured for mounting the functional bezel to the optical drive.

32. (Previously presented) The computer system of claim 25 wherein the first attachment feature of the functional bezel matches the second attachment feature.

33. (Previously presented) The computer system of claim 25 wherein the disk guide facilitates proper attachment of the optical disk into the optical drive.

34. (Previously presented) The computer system of claim 25 wherein the disk guide includes a ramp feature to point the optical disk down into the optical drive during injection and to point the optical disk up during ejection.

35. (Previously presented) The computer system of claim 25 wherein the second opening in the cosmetic bezel is larger than the first opening in the functional bezel to facilitate injection or ejection of the optical disk.

36. (Previously presented) The computer system of claim 25 wherein the functional bezel facilitates slot loading of the optical disk into the optical drive.